

Synthes 4.5 mm Cannulated Screw Instrument and Implant Set (105.04)

Instruments and Storage

Catalog #	Description
292.72	1.6 mm Threaded Guide Wire, gold, 150 mm (10)
310.16	1.5 mm Drill Bit, quick coupling, 110 mm
310.65	3.2 mm Cannulated Drill Bit, quick coupling, 170 mm (2)
310.66	4.5 mm Cannulated Drill Bit (2)
310.85	Cannulated Countersink
311.44	T-Handle with quick coupling
311.59	Cannulated Tap
312.46	4.5 mm/3.2 mm Double Drill Sleeve
312.73	Adjustable Parallel Wire Guide
312.74	1.6 mm Trocar, 59 mm length
312.75	3.2 mm/1.6 mm Drill Sleeve, 52 mm length
312.76	7.0 mm/3.2 mm Drill Sleeve, 46 mm length
312.77	9.5 mm/7.0 mm Protection Sleeve, 39 mm length
314.15	Large Hexagonal Screwdriver Shaft
314.20	Cannulated Hexagonal Screwdriver
314.31	Holding Sleeve, for Cannulated Hexagonal Screwdriver (314.20)
319.17	Cannulated Screw Measuring Device
319.35	1.6 mm Cleaning Stylet
319.97	Screw Forceps
304.220	4.5 mm Cannulated Screw Instrument and Implant Set Graphic Case (for Set 105.04)
304.223	Rack for 4.5 mm Cannulated Screws

219.91 Washers, 10.0 mm (5)

4.5 mm Cannulated Screws, partially threaded, stainless steel

Catalog #	Length
214.420	20 mm (3)
214.422	22 mm (3)
214.424	24 mm (3)
214.426	26 mm (3)
214.428	28 mm (3)
214.430	30 mm (3)
214.432	32 mm (3)
214.434	34 mm (3)
214.436	36 mm (2)
214.438	38 mm (3)
214.440	40 mm (3)
214.442	42 mm (3)
214.444	44 mm (2)
214.448	48 mm (3)
214.452	52 mm (3)
214.456	56 mm (3)
214.460	60 mm (3)
214.464	64 mm (3)
214.468	68 mm (3)
214.472	72 mm (3)

4.5 mm Cannulated Screws, fully threaded, stainless steel

Catalog #	Length
214.620	20 mm (2)
214.622	22 mm (2)
214.624	24 mm (2)
214.626	26 mm (2)
214.628	28 mm (2)
214.630	30 mm (2)
214.632	32 mm (2)
214.634	34 mm (2)
214.636	36 mm (2)
214.638	38 mm (2)
214.640	40 mm (1)
214.642	42 mm (2)
214.644	44 mm (2)
214.648	48 mm (2)
214.652	52 mm (2)
214.654	54 mm (2)
214.656	56 mm (2)
214.660	60 mm (2)
214.664	64 mm (2)
214.668	68 mm (2)
214.672	72 mm (2)